(30) Priority data:

# WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



F11

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

			1011 1112/111 (101)
(51) International Patent Classification 5:	ı	(11) International Publication Number:	WO 92/13491
A61B 17/064	A1	(43) International Publication Date:	20 August 1992 (20.08.92)
A			

(21) International Application Number: PCT/US92/00209
(22) International Filing Date: 8 January 1992 (08.01.92)

653,353 6 February 1991 (06.02.91) US

(71) Applicant: MINNESOTA MINING AND MANUFAC

(71) Applicant: MINNESOTA MINING AND MANUFAC-TURING COMPANY [US/US]; 3 M Center, Post Office Box 33427, Saint Paul, MN 55133-3427 (US).


(72) Inventors: VIDAL, Claude; REDMOND, Russell, J.; P.O. Box 33427, Saint Paul, MN 55133-3427 (US).

(74) Agents: HOHENSHELL, Jeffrey, J. et al.; P.O. Box 33427, Saint Paul, MN 55133-3427 (US). (81) Designated States: AT (European patent), BE (European patent), CA, CH (European patent), DE (European patent), DK (European patent), ES (European patent), FR (European patent), GB (European patent), GR (European patent), IT (European patent), JP, LU (European patent), MC (European patent), NL (European patent), SE (European patent).

Published

With international search report.

(54) Title: IMPROVED SURGICAL HARDWARE WITH BACTERIOSTATIC SILVER COATING, AND METHOD OF USING SAME



(57) Abstract

A staple, wire suture, clip, or ther item of surgical hardware is disclosed which can be used to close a wound, made from a high strength metal to have a low profile design to minimize interference and disturbance of the wound, and having a bacteriostatic silver coating to reduce the risk of wound infection from the hardware. A method of closing surgical wounds with reduced risk of infection is also disclosed, the method includes the steps of closing the wound with a staple, wire suture, clip, or ther item of surgical hardware made from a high strength metal that has a silver coating.

#### FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FI	Finland	MI	Mali
AU	Australia	FR	France	MN	Mongolia
BB	Burbaiko	GA	Ciabon	MR	Mauritania
38	Belgium	GB	United Kingdom	MW	Malawi
8F	Burkina Faso	GN	Guinea	NL	Nutherlands
BG	Bulgaria	GR	Greece	NO	Norway
BJ	Benin	HU	Hungary	PL	Poland
BR	Brazil	31	Ircland	RO	Romania
CA	Canada	IT	ltaly	RU	Russian Federation
CF	Central African Republic	JP	Japan	SD	Sudan
CC	Congo	KP	Democratic People's Republic	SB	Sweden
СН	Switzerland		of Korea	SN	Sonegal
CI	Côte d'Ivaire	KR	Republic of Korea	SU	Soviet Union
СМ	Cameroon	LI	l icchtenstein	TD	Chad
CS	Czechoslovakia	LK	Sri Lanka	TG	Tugo
DE	Ciermany	LU	Luxembourg	us	United States of America
DK	Denmark	MC	Monaco		
ES	Spain	MG	Madagascar		

WO 92/13491 PCT/US92/00209

# IMPROVED SURGICAL HARDWARE WITH BACTERIOSTATIC SILVER COATING, AND METHOD OF USING SAME

#### 5 BACKGROUND OF THE INVENTION

10

15

20

25

30

This invention relates to surgical hardware of the type used to close wounds, and to an improved method of closing wounds using such hardware.

Various items of metal hardware have been developed to assist in closing wounds. At one time such hardware was made from solid silver. However, because of silver's high ductility and relatively low strength, silver hardware had to be made very coarse to have adequate mechanical properties. For many applications solid silver hardware was objectionably coarse. High strength metals such as stainless steel and titanium, permit more slender, clinically desirable hardware designs, and have for decades been the state of the art materials for surgical hardware.

Wound infection is always a serious concern because of its system-wide effect and retardation of normal wound healing, but when surgical hardware is required and used there are additional potential complications from wound infection including dehiscence or splitting of the wound, leakage from the wound, and formation of adhesions. While conventional steel and titanium hardware can be sterilized, it does not appear to have significant bacteriostatic effect, and may actually promote infection compared with other materials. Nevertheless, because these high strength metals permit the manufacture of such small, high strength hardware, these metals are still widely used.

#### SUMMARY OF THE INVENTION

35 The present invention provides an improved item of surgical hardware that provides the strength and compact size of a high strength metal such as stainless steel or titanium, and bacteriostatic properties t reduce the risk of wound infection. This hardware all ws w unds to be

10

15

20

25

30

n atly and effectively closed, and provides some bacteri static action that reduces the risk of many of the complications encountered in the use of surgical hardware.

The invention relates to a staple, wire suture, clip, or other item of surgical hardware used in closing wounds. Generally, the surgical hardware constructed according to the principles of the present invention comprises an item of surgical hardware that is made from a high strength metal, for example stainless steel or titanium, and which has a silver coating. The silver coating may be either silver plating, or a coating of silver salt. Generally the method of closing wounds according to the present invention comprises closing the wounds with surgical hardware made from a high strength metal and which has a silver coating.

The hardware of the present invention provides all of the advantages of being constructed from a high strength metal, including high strength and compact size, and the additional benefit of bacteriostatic action which helps to reduce the risk of complications resulting from the use of the hardware. The compact design permitted by the present invention ensures that the hardware has sufficient strength to hold the wound closed, and a sufficiently compact size that it does not unduly disturb the wound site or interfere with healing. The cost of manufacturing hardware according to the principles of the present invention is only the cost of manufacturing marginally higher than conventional hardware. The method of this invention provides a way to close wounds with reduced risk of infection and complications.

These and other features and advantages will be in part apparent and in part pointed out hereinafter.

#### BRIEF DESCRIPTION OF THE DRAWINGS

35 FIGURE 1 is a perspective view of an internal (soft tissue) staple constructed according to the principles of this invention;

WO 92/13491

5

10

30

35

PCT/US92/00209

FIGURE 2 is a perspective view of a skin staple constructed according to the principles of this invention;

3

FIGURE 3 is a perspective view of a fascia staple constructed according to the principles of this invention;

FIGURE 4 is a. perspective view of a vascular staple constructed according to the principles of this invention;

FIGURE 5 is a perspective view of a vascular clip constructed according to the principles of this invention;

FIGURE 6 is a perspective view of a wire suture constructed according to the principles of this invention; and

FIGURE 7 is a cross-sectional view of the wire suture, taken along the plane of line 7-7 in Figure 6.

Corresponding reference numerals indicate corresponding parts throughout the several views of the drawings.

### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Surgical staples constructed according principles of the present invention are indicated generally 20 as 20, 22, 24, and 26 in Figures 1 - 4. A surgical clip constructed according to the principles of the present invention is indicated generally as 28 in Figure 5. A wire suture constructed according to the principles of the present invention is indicated generally as 30 in Figure 6. 25 Although the present invention is described with respect to staples, clips, and sutures, the invention is not so limited and relates to any item of surgical hardware of the type used to close wounds.

The staples 20 - 26, the clip 28, and the suture 30 are made from a high strength surgical metal such as a stainless steel or titanium. Because they are constructed of a high strength material, these items have superior strength, and more importantly they can be designed to be small and compact so that they do not unnecessarily disturb the wound or interfere with proper healing. However, unlike any prior art item of surgical hardware, the staples 20 - 26, the clip 28, and the wire suture 30 have a silver coating. This is best shown in Figure 7 where the suture is shown as

10

15

20

25

30

comprising high strength surgical metal 32 with a silver coating 34. The silv r c ating provides a bacteriostatic action that inhibits infection. Thus infection is less lik ly to propagate when the surgical hardware of the present invention is used, and thus there is a reduced risk from infection-related complications from the use of such hardware.

The silver coating may be silver plating applied by a hot dip or electro-deposition process, or some other method. Alternatively, the coating may be a silver salt applied to the exterior of the item of hardware, for example silver nitrate, or silver-zinc allantoinate.

The method of the present invention relates to an improved method of closing surgical wounds with reduced risk of infection. The method comprises the step of closing the wound with a staple, wire suture, clip or other item of surgical hardware made from a high strength metal that has a silver coating.

The bacteriostatic effect of the hardware of this invention was tested by introducing a silver coated staple according to the principles of this invention, a stainless steel staple, and titanium staple into two difference agar media: Trypticase Soy Sheep Agar and Mueller Hinton Agar. Each of the staples was screened against staph aureus, coli, Pseudomonas aeriginosa, Escherichia The plates were inoculated with a standard faecales. turbidity of a 0.5 McFarland standard. The staples were placed on top of the agar and the plates were incubated at 35°C for 24 hours. As illustrated in the following table, only the silver coated staple of the present invention showed any bacteriostatic action showing a zone inhibition around the staple.

35		Staphaureus		Escherichia Coli		Pseudomonas Aeriginosa		Strep <u>Faecales</u>	
40	Silver Plated	TSS Agar 11mm	M-H Agar 11mm	TSS Agar 6mm	M-H Agar	TSS Agar 22mm?	M-H Agar	TSS Agar	M-H Agar
40	Stainless Steel	•••	•••	•••	•••	•••	•••	•••	•••
	Titanium	•••	•••	• • •	• • •	•••	•••	• • •	

WO 92/13491 PCT/US92/00209

In view of the above, it will be seen that the several objects of the invention are achieved and other advantageous results attained.

5

As various changes could be made in the above constructions without departing from the scope of the invention, it is intended that all matter contained in the above description or shown in the accompanying drawings shall be interpreted as illustrative and not in a limited

10 sense.

5

30

#### WHAT IS CLAIMED IS:


- 1. An improved staple, wire suture, clip, or other metallic item of surgical hardware of the type mad from a high strength metal such as stainless steel or titanium, the improvement comprising a silver coating on the surface of the hardware.
- The hardware according to claim I wherein the
   silver coating comprises silver plating.
  - 3. The hardware according to claim 1 wherein the silver coating comprises silver salts.
- 4. A staple, wire suture, clip, or other item of surgical hardware used to close a wound, made from a high strength metal to have a low profile design to minimize interference and disturbance of the wound, and having a bacteriostatic silver coating to reduce the risk of wound infection from the hardware.
  - 5. The hardware according to claim 4 wherein the silver coating comprises silver plating.
- 25 6. The hardware according to claim 4 wherein the silver coating comprises silver salts.
  - 7. A method of closing surgical wounds with reduced risk of infection comprising the step of closing the wound with a staple, wire suture, clip or other item of surgical hardware made from a high strength metal that has a silver coating.
- 8. The method according to claim 4 wherein the silver coating comprises silver plating.
  - 9. The method according to claim 4 wherein the silver coating comprises silver salts.

- 10. A surgical staple having bacteriostatic c ating.
- 11. A surgical staple according to claim 1 wherein said bacteriostatic coating is silver.

F.IG. 1.



FIG. 2.



*FIG.3.* 







FIG. 4.



FIG. 7.







International Application No.

		ECT MATTER (If several classification s		·
	to International Patent . 5 A61B17/0	t Classification (IPC) or to both National C 64	· excentration and IPC	
II. FIELDS	SEARCHED			
		Minheum Docume	estation Searched	
Classificat	ion System		Classification Symbols	
Int.Cl	. 5	A61B		
		Documentation Searched other to the Extent that such Documents a		
			_	
m. Docu	MENTS CONSIDERE	D TO BE RELEVANT		
Category *	Citation of De	ocument, <sup>11</sup> with indication, where appropris	ite, of the relevant passages 12	Relevant to Claim No.13
X		206 024 (BECTON) 30 Dec ims 1,4,11,12,14	ember 1986	1-11
A	EP,A,O a	255 248 (MINNESOTA) 3 F	ebruary 1988	3,6,9
A	CH,A,654	4 738 (BLÄTTLER) 14 Mar	ch 1986	,
A	WO,A,8	102 668 (BURFORD) 1 Octa	ober 1981	
A	EP,A,O	328 421 (CULUMBIA) 16 A	ugust 1989	
A	EP,A,0 (	046 715 (USSC) 3 March :	1982	
A	EP,A,0 4	406 014 (ETHICON) 2 Jan	uary 1991	
			_	
-	categories of cited do		"I" later document published after the intern- or priority date and not in conflict with t	
COM	sidered to be of partic		cited to understand the principle or these invention	A smeanling are
	lier document but publi ng date	shed on or after the interactional	"I" document of particular relevances the cia cannot be considered nevel or cannot be	med invention considered to
"L" doc	ument which may throu ch is cited to establish	r doubts on priority claim(s) or the publication date of another	involve an inventive step "Y" document of particular relevance; the cia	
dts	tion or other special re		cannot be considered to involve an invent document is combined with one or more	ive step when the ther such docu-
oth To doo	er meens	to the interestional filing date but	ments, such combination being obvious to in the art. "A" document member of the same patent fan	a person skilled
IV. CERTI	FICATION			
		he laternational Search	Date of Mailing of this International Seas	ch Report
	·	PRIL 1992	6. 05. 92	2
International	Searching Authority		Signature of Authorized Officer	2
	EUROPEA	N PATENT OFFICE	BARTON S.	ten

# ANNEX TO THE INTERNATIONAL SEARCH REPORT 9200209 9200209 SA

56283

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report.

The members are as contained in the European Patent flice EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information. 27/04/92

Patent document cited in search report	Publication date		Patent family member(s)		Publicatios date
EP-A-0206024	30-12-86	US-A-	4886505	12	2-12-89
LI A OLOGOLI	<b></b>	AU-A-	3155089	29	-06-89
		au-b-	588 <b>598</b>		-09-89
		AU-A-	5841786		-12-86
		JP-B-	2005089		-01-90
		JP- <b>A</b> -	62002947	08 	-01-87
EP-A-0255248	03-02-88	US-A-	4728323		-03-88
<b></b>		AU-B-	595333		-03-90
		AU-A-	7427987		-01-88
		CA-A-	1279573		-01-91
		JP-A-	63035260	15	-02-88
CH-A-654738	14-03-86	None			
WO-A-8102668	01-10-81	EP-A,B	0048246		-03-82
		EP-A,B	0048247		-03-82
		WO-A-	8102667		-10-81
		GB-A,B	2072514		-10-81
•	• •	GB-A,B	2073024		-10-81
		US-A-	4476590		-10-84
		US-A-	4615705	<del></del>	-10-86
EP-A-0328421	16-08-89	US-A-	5019096		-05-91
F! \\ 0450.55		AU-A-	2989589		-08-89
		JP-A-	2017071		-01-90
		AU-A-	7922991	03-	-10-91
EP-A-0046715	03-03-82	AT-T-	7848		-06-84
L. 7. 0010720		AU-A-	7101681		-03-82
		CA-A-	1170536		-07-84
		DE-C-	3152256		-02-85
		GB-A,B	2100821	-	-01-83
		WO-A-	8200582		-03-82
		US-A-	4407286 		·10-83
EP-A-0406014	02-01-91	AU-A-	5788390		01-91
		CA-A-	2020075		12-90
L. 74 0100011		JP-A-	3066378	22_	·03 <b>-</b> 91

FORM POCT

For more details about this samex : see Official Journal of the European Patent Office, No. 12/82